



PRODUCT SPECIFICATION SHEET

Banico Solenoid Valves

TOP SPEC:

Suitable For Water, Oil, Air,
Inert Gases And Other Fluids

PAGE

1/1

Product Description

Solenoid valves from Banico are suitable for water, oil, air, inert gases and other fluids non-corrosive for copper alloys, with viscosity up to 2 Engler.

BSP F x F, mains operated directly activated water solenoid valve with brass body and stainless steel plunger. Normally closed directly activated valve supplied complete with 240V actuator coil and Din connector.



Main Features

- Suitable for water, oil, air, inert gases and other fluids
- Normally closed 2 way valve
- Direct activation
- 1/4 - 1" BSP sizes available

Installation & Operation

- Normally closed
- Direct Activation
- Female Connections, size 1/4" to 1" BSP
- Energized Coil Opens the Plug

Additional Information

Part Number

1/4" BSP Female with 240v Coil	FV20-635
3/8" BSP Female with 240v Coil	FV20-640
1/2" BSP Female with 240v Coil	FV20-641
3/4" BSP Female with 240v Coil	FV20-642
1" BSP Female with 240v Coil	FV20-643
71°C Electro Thermal Link	FV20-170
Replacement Coil for Solenoid Valves	FV20-650



Replacement Coil for Solenoid Valves
(FV20-650. Sold Separately)

NEED MORE INFORMATION?

○ 01373 822220

○ sales@fueldump.co.uk

○ www.fueldump.co.uk