Osprey Nozzle



Automatic shut-off nozzle for over-the-wing fueling of aircraft.

- Specifically designed for business and private overthe-wing aviation fueling.
- · Automatic shut-off when wing tanks are full.
- Easy to remove and clean fuel 100 mesh SS fuel filter assembly.
- · Nozzle comes with red full grip guard to identify use only with aviation fuel or black full grip guard for jet fuel application if desired.
- Complies with EI1540 and NFPA 407.

Osprey Nozzle with NPT

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS. (KG)
1149812N^	without Hold Open Clip and Spout Bushing, with Waffle Splash Guard and mesh filter 4.6 (2.0)	
		^ NOT LISTED


Osprey Nozzle with BSPP

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS. (KG)
1149840N^	without Hold Open Clip and Spout Bushing, with Waffle Splash Guard and mesh filter 4.6 (2.0)	
		^ NOT LISTED

Construction

Body	Aluminum
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon®
Lever	One piece contoured steel
Inlet	1" / 25.4 mm NPT and BSPP









Osprey Nozzle

Automatic shut-off nozzle for over-the-wing fueling of aircraft.


Dimensions and System Options

Swivels

MODEL NO.	DESCRIPTION	
008517	1" M x 1" F NPT Single Plane Swivel	
004860	1" M x 1" F NPT Multi-Plane High Flow Swivel	
003306	1" M x 1" F BSPP Multi-Plane Swivel	
006949	1" M x 1" F BSPP Multi-Plane High Flow Swivel	

Accessories

MODEL NO.	DESCRIPTION
011817	Electrical Grounding Plug
012141	Osprey Spout Assembly Kit
011946	Spout Cap Assembly
012148	Strainer BSP Kit
012143	Strainer NPT Kit





2325 Husky Way • Pacific, MO 63069 (800) 325-3558 • Fax (636) 825-7300 www.husky.com • sales@husky.com

