



SPECIFICATION SHEET

DELIVERY HOSE FOR DISPENSING DEF/ADBLUE®

CONTACT:

01373 822220

sales@fueldump.co.uk

DESCRIPTION

Soft PVC hose with POLYURETHANE (PU) underlayer with polyester yarn reinforcement and PU adhesive middle layer, for pressurized transfer of oil, diesel oil, blue diesel, urea (ISO 22241).

Ø nominal mm	Ø nominal inch	Ø i.d. mm	Ø o.d. mm	working pressure at 23° bar	working press. at 40° bar	working press. at 60° bar	bursting press. at 23° bar	bending radius mm	total thickness mm	weight meter g/m	# wires for angle n° x a°	coil length m
12.7	1/2	12,7	18.5	15	10	6	45	80	2.9	205	18x54°	60
13		13	21	15	10	6	45	100	4	270	18x54°	50
19	3/4	19	26	15	10	6	45	130	3.5	350	24x54°	50
25	1	25	35	15	10	6	45	180	5	670	36x54°	50

	SMOOTH SURFACE	*****
	FLEXIBILITY	***
	ABRASION RESISTANCE	***
	TEMPERATURE RANGE	-10 °c 60 °c
	CHEMICAL RESISTANCE	PU Table
	CRUSHING RESISTANCE	***



PART NUMBER	DESCRIPTION	PRICE
GFH3550-POL	3/4" Delivery Hose (Priced per Meter) - For Dispensing DEF/Urea/AdBlue®	£3.50pm

NEED MORE INFO?
Visit us on www.fueldump.co.uk